

| <b>MODEL NO.</b>                | <b>H-26/42</b>                     |
|---------------------------------|------------------------------------|
| <b>12° canted head</b>          |                                    |
| Rectangle:                      | 26" x 42"                          |
| Round:                          | 30" diameter                       |
| Straight head:                  | 32" x 42"                          |
|                                 | Cuts all 40" beams                 |
| <b>Blade Dimensions:</b>        |                                    |
| Length:                         | 33'                                |
| Width:                          | 2-5/8"                             |
| Thickness:                      | .063"                              |
| <b>Blade Drive:</b>             | 20 hp                              |
| <b>Hydraulic Drive:</b>         | 3 hp                               |
| <b>Blade Speed:</b>             | 75-300 SFM                         |
| <b>Blade Wheel Diameter:</b>    | 38"                                |
| <b>Blade Guides:</b>            | Carbide                            |
| <b>Hydraulic Tank Capacity:</b> | 9.5 U.S. Gallons                   |
| <b>Hydraulic Sytem:</b>         | 1,300 psi                          |
| <b>Coolant Tank Capacity:</b>   | 30 U.S. Gallons                    |
| <b>Vise Control:</b>            | Hydraulic (full stroke)            |
| <b>Table Height:</b>            | 38"                                |
| <b>Machine Workload:</b>        | 30,000 lbs                         |
| <b>Machine Weight:</b>          | 21,000 lbs                         |
| <b>Machine Dimensions:</b>      | 217" wide<br>82" long<br>137" high |