

Model No.:	M-16A	M-16P	M-20A	M-20AP	M-20A-120
Capacity					
90° Rectangle:	16" h x 25" w	16" h x 25"w	20" h x 30" w	20" h x 30" w	20" h x 30" w
90° Round:	16" diameter	16" diameter	20" diameter	20" diameter	20" diameter
45° Rectangle:	15" x 16"	15" x 16"	19" x 20"	19" x 20"	19" x 20"
45° Round:	16" diameter	16" diameter	20" diameter	20" diameter	20" diameter
60° Rectangle:	9" x 16"	9" x 16"	12" x 20"	12" x 20"	12" x 20"
60° Round:	11" diameter	11" diameter	14" diameter	14" diameter	14" diameter
Bundling Capacity (optional):	16" x 25"	16" x 25"	20" x 30"		
Blade					
Length:	18'6"	18'6"	20'6"	20'6"	20'6"
Width:	1¼"	1¼"	1½"	1½"	1½"
Thickness:	.042"	.042"	.050"	.050"	.050"
Blade Speed:	50-350 SFM (vfd)	50-350 SFM (vfd)	50-350 SFM (vfd)	50-350 SFM (vfd)	50-350 SFM (vfd)
Blade Guides:	Carbide	Carbide	Carbide	Carbide	Carbide
Blade Wheel Diameter:	19"	19"	22"	22"	
Blade Drive:	7.5 hp	7.5 hp	10 hp	10 hp	10 hp
Hydraulic Drive:	3 hp	3 hp	3 hp	3 hp	3 hp
Hydraulic System:	900 psi	900 psi	900 psi	900 psi	900 psi
Hydraulic Tank Capacity:	11 U.S. Gallons	11 U.S. Gallons	11 U.S. Gallons	11 U.S. Gallons	11 U.S. Gallons
Coolant Tank:	9 U.S. Gallons	9 U.S. Gallons	9 U.S. Gallons	9 U.S. Gallons	9 U.S. Gallons
Shuttle Stroke:	0-33" single stroke - multi-indexing standard	n/a	0-33" single stroke - multi-indexing standard	n/a	0 -120" multi-indexing standard
Vise Control:	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Table Height:	32"	32"	32"	32"	32"
Maximum Work Load:	8,000 lbs	8,000 lbs	8,000 lbs	8,000 lbs	8,000 lbs
Machine Weight:	7,400 lbs	7,200 lbs	7,700 lbs	7,500 lbs	12,700 lbs
Dimensions:	132" wide 90" long 66" high	132" wide 90" long 66" high	140" wide 90" long 66" high	140" wide 90" long 66" high	140" wide 90" long 66" high