

<b>Model No.</b>	<b>S-23P</b>	
<b>Capacity</b>		
90° Rectangle:	16" x 18"	406 mm x 457 mm
90° Round:	16" diameter	406 mm diameter
45° Rectangle:	16" x 10"	406 mm x 254 mm
45° Round:	12" diameter	305 mm diameter
60° Rectangle:	16" x 6"	406 mm x 152 mm
60° Round:	8"	203 mm
<b>Blade</b>		
Length:	15'6"	4724 mm
Width:	1 1/4"	32 mm
<b>Blade Speed:</b>	75-350 SFM	22-107 m/min
<b>Blade Guides:</b>	Carbide	Carbide
<b>Blade Wheel Diameter:</b>	19"	483 mm
<b>Mitering Capability:</b>	90° to 60°	90° to 60°
<b>Blade Drive:</b>	5 hp	3.7 kW
<b>Hydraulic Drive:</b>	2 hp	1.5 kW
<b>Hydraulic Tank Capacity:</b>	7 U.S. Gallons	liters
<b>Coolant Tank:</b>	6 U.S. Gallons	23 liters
<b>Vise Control:</b>	Hydraulic	Hydraulic
<b>Table Height:</b>	31"	787 mm
<b>Maximum Work Load:</b>	5,000 lbs	2268 kg
<b>Machine Weight:</b>	2,400 lbs	1043 kg
<b>Dimensions:</b>	97" wide	2462 mm wide
	70" long	1778 mm long
	63" high	1600 mm high