

Model No.	V25-APC	
Capacity		
90° Rectangle:	30" x 25"	762 mm x 635 mm
90° Round	25" diameter	635 mm diameter
90° Square:	25" x 25"	635 mm x 635 mm
45° Rectangle:	21" x 25"	533 mm x 635 mm
45° Round:	21" diameter	533 mm diameter
45° Square:	21" x 21"	533 mm x 533 mm
60° Rectangle (right):	14-1/2" x 25"	368 mm x 635 mm
60° Round (right):	14-1/2" diameter	368 mm diameter
60° Square (right):	14-1/2" x 14-1/2"	368 mm x 368 mm
60° Rectangle (left):	13-1/2" x 25"	343 mm x 635 mm
60° Round (left):	13-1/2"	343 mm
60° Square (left):	13-1/2" x 13-1/2"	343 mm x 343 mm
Blade		
Length:	21' 0.5"	6410 mm
Width:	1-1/2"	38 mm
Thickness:	0.050"	1.3 mm
Blade Drive:	10 hp	7.5 kW
Blade Speed:	75-350 SFM	23-107 m/min
Band Wheel Diameter:	32" (Drive Wheel) 24" (Idler)	812" (Drive Wheel) 609" (Idler)
Motor Voltage:	As Specified by Customer	
Hydraulic Drive:	3 Hp, 1200 PSI	2.2 kW, 8274 kPa
Hydraulic Tank Capacity:	7 U.S. Gallons	26 liters
Coolant Tank:	38 U.S. Gallons	141 liters
Table Height:	44"	1073 mm
Maximum Work Load:	5,000 lbs	2270 kg
Machine Weight:	15,000 lbs	6805 kg