

| Model No.                                | V-25                                |  |
|--|-------------------------------------|--|
| <b>Capacity</b>                          |                                     |  |
| 90° Rectangle:                           | 30" x 25"                           | 762 mm x 635 mm                              |
| 90° Round                                | 25" diameter                        | 635 mm diameter                              |
| 90° Square:                              | 25" x 25"                           | 635 mm x 635 mm                              |
| 45° Rectangle:                           | 21" x 25"                           | 533 mm x 635 mm                              |
| 45° Round:                               | 21" diameter                        | 533 mm diameter                              |
| 45° Square:                              | 21" x 21"                           | 533 mm x 533 mm                              |
| 60° Rectangle (right):                   | 14-1/2" x 25"                       | 368 mm x 635 mm                              |
| 60° Round (right):                       | 14-1/2" diameter                    | 368 mm diameter                              |
| 60° Square (right):                      | 14-1/2" x 14-1/2"                   | 368 mm x 368 mm                              |
| 60° Rectangle (left):                    | 13-1/2" x 25"                       | 343 mm x 635 mm                              |
| 60° Round (left):                        | 13-1/2"                             | 343 mm                                       |
| 60° Square (left):                       | 13-1/2" x 13-1/2"                   | 343 mm x 343 mm                              |
| <b>Blade</b>                             |                                     |  |
| Length:                                  | 21' 0.5"                            | 6410 mm                                      |
| Width:                                   | 1-1/2"                              | 38 mm  |
| Thickness:                               | 0.050"                              | 1.3 mm                                       |
| <b>Blade Drive:</b>                      | 10 hp                               | 7.5 kW                                       |
| <b>Blade Speed:</b>                      | 75-350 SFM                          | 23-107 m/min                                 |
| <b>Band Wheel Diameter:</b>              | 32" (Drive Wheel)<br>24" (Idler)    | 812" (Drive Wheel)<br>609" (Idler)           |
| <b>Motor Voltage:</b>                    | As Specified by Customer            |  |
| <b>Hydraulic Drive:</b>                  | 3 Hp, 1200 PSI                      | 2.2 kW, 8274 kPa                             |
| <b>Hydraulic Tank Capacity:</b>          | 7 U.S. Gallons                      | 26 litres                                    |
| <b>Coolant Tank:</b>                     | 38 U.S. Gallons                     | 141 litres                                   |
| <b>Table Height:</b>                     | 44"                                 | 1073 mm                                      |
| <b>Maximum Work Load:</b>                | 10,000 lbs                          | 4537 kg                                      |
| <b>Machine Weight:</b>                   | 10,000 lbs                          | 4537 kg                                      |
| <b>Dimensions:</b>                       | 97" wide<br>152" long<br>123" high  | 2462 mm wide<br>3858 mm long<br>3122 mm high |
| <b>Dimensions with Full Miter Swing:</b> | 141" wide<br>152" long<br>123" high | 3579 mm wide<br>3858 mm long<br>3122 mm high |